NSN 5935-00-131-0837

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-131-0837 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.093 inches **Overall Diameter:** 0.750 inches **Cable Entrance Diameter:** 0.116 inches **Distance From Mounting Shoulder To Front Face:** 0.719 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin **Connector Cable Strain Relief Method:** Compression nut Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Rubber synthetic single mating end **Terminal Type:** Solder well single mating end single contact grouping

NSN 5935-00-131-0837

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Copper alloy
Shell Surface Treatment:
Gold and copper
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surface and body surface gold
Precious Material And Weight:
0.105 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0