

View Online at <https://aerobasegroup.com/nsn/5935-00-131-5339>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Bushing Diameter:**

Between 0.620 inches and 0.630 inches

**Overall Height:**

Between 0.985 inches and 1.005 inches

**Overall Width:**

Between 0.985 inches and 1.005 inches

**Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.120 inches and 0.130 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.713 inches and 0.723 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.713 inches and 0.723 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.721 inches and 0.751 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

N single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.625 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Copper alloy

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Special Features:**

No. 16 awg wire permanently soldered in from solder well terminal to case

**Precious Material And Location:**

Contact surface gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.