
## NSN 5935-00-131-9693

Tip Jack - Page 1 of 2

**Electrical Insulation Feature:** 

Insulated from panel

5.0



**Identification Code Color:** Black **Body Style:** Terminal mounted **Overall Length:** 0.460 inches **Terminal Length:** 0.156 inches **Overall Height:** 0.386 inches **Overall Width:** 0.156 inches **Distance Between Mounting Facility Centers:** 0.400 inches Maximum Voltage Rating In Volts: 1500.0 ac Accommodated Finger Type: Test prod single finger Finger Accommodation Diameter: 0.080 inches single finger **Finger Accommodation Length:** 0.500 inches single finger **Current Rating In Amps:** Mounting Facility Type And Quantity: 1 terminal **Terminal Type:** Tab, solder lug Material: Copper alloy terminal Material: Plastic polyamide insulator **Precious Material And Location:** Spring contact surface gold **Precious Material:** Gold Surface Treatment: Gold spring **Surface Treatment:** Gold spring



## NSN 5935-00-131-9693

Tip Jack - Page 2 of 2



## **Test Data Document:**

81349-mil-c-39024 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-39024 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03400