Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-131-9834

# **Thread Class:**

2a and 2b

# **Thread Direction:**

Right-hand

# **Body Style:**

Straight shape w/screw locks

## **Overall Length:**

1.250 inches

#### **Overall Height:**

0.910 inches

## **Overall Width:**

0.380 inches

# **Environmental Protection:**

Heat resistant and cold resistant and shock resistant and salt water resistant and vibration resistant

# Threaded Device Type:

Coupling facility

# Mating End Quantity:

1

# **Contact Position Arrangement Style:**

Lk-34hv4 single mating end

# **Contact Removability:**

Nonremovable single mating end single contact grouping

# **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

#### **Polarization Method:**

Jackscrew

# **Connector Locking Method:**

Jackscrew-socket

# **Operating Tempurature Rating:**

Between -54.0 degrees celsius and 100.0 degrees celsius

# Thready Qty Per Inch (tpi):

56

# Thread Size:

0.086 inches

# **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

# Insert Material:

Plastic diallyl phthalate glass filled single mating end

# NSN 5935-00-131-9834

Electrical Plug Connector - Page 2 of 2



**Contact Surface Treatment Specification:** Mil-g-45204, ty ii, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Insert Material Specification:** Mil-p-19833, ty gdi-30 military specification single material response single mating end **Included Contact Quantity:** 34 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.034 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.