

NSN 5935-00-131-9991 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-131-9991 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 0.547 inches **Overall Diameter:** 0.312 inches **Distance From Mounting Shoulder To Front Face:** 0.172 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Mating end **Connector Locking Method:** Friction Thready Qty Per Inch (tpi): 28 Thread Size: 0.250 inches

Back single mating end single contact grouping

Contact Material:

Terminal Location:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

NSN 5935-00-131-9991

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 2 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round w/flat **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.002 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):