NSN 5935-00-132-2308



| TIP Jack - Page 1 of 2 | |
|---|--|
| View Online at https://aerobasegroup.com/nsn/5935-00-132-2308 | |
| Electrical Insulation Feature: | |
| Insulated from panel | |
| Identification Code Color: | |
| Gray | |
| Body Style: | |
| Terminal mounted | |
| Overall Length: | |
| 0.460 inches | |
| Terminal Length: | |
| 0.156 inches | |
| Overall Height: | |
| 0.386 inches | |
| Overall Width: | |
| 0.156 inches | |
| Distance Between Mounting Facility Centers: | |
| 0.400 inches | |
| Maximum Voltage Rating In Volts: | |
| 1500.0 ac | |
| Accommodated Finger Type: | |
| Test prod single finger | |
| Finger Accommodation Diameter: | |
| 0.080 inches single finger | |
| Finger Accommodation Length: | |
| 0.400 inches single finger | |
| Current Rating In Amps: | |
| 5.0 | |
| Mounting Facility Type And Quantity: | |
| 1 terminal | |
| Terminal Type: | |
| Tab, solder lug | |
| Material: | |
| Copper alloy terminal | |
| Material: | |
| Plastic polyamide insulator | |
| Precious Material And Location: | |
| Spring contact surface gold | |

Precious Material:

Gold

Surface Treatment:

Gold spring

Surface Treatment:

Gold spring

NSN 5935-00-132-2308

Tip Jack - Page 2 of 2



Test Data Document:

81349-mil-c-39024 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

| | specification |
|--|---------------|
| | |
| | |
| | |

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03400