## NSN 5935-00-132-2594

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-132-2594

**Body Style:** 

Straight shape

**Overall Length:** 

Between 2.714 inches and 2.744 inches

**Overall Height:** 

0.660 inches

**Overall Width:** 

Between 0.479 inches and 0.509 inches

**Environmental Protection:** 

Moisture resistant and vibration resistant and salt water resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.081 inches and 0.091 inches

**Distance Between Mounting Facility Centers:** 

Between 2.495 inches and 2.505 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

"c, 27w2" single mating end

**Contact Removability:** 

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end 1st contact grouping

**Polarization Method:** 

Mating end

Shell Type:

Solid

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:** 

Gold and silver single mating end all contact groupings

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Solder well single mating end all contact groupings

**Shell Material:** 

Steel

**Shell Surface Treatment:** 

Cadmium and chromate

**Insert Material Specification:** 

Mil-m-19833, ty gdi-30f military specification single material response single mating end

## NSN 5935-00-132-2594

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quan	tity:
-----------------------	-------

25 single mating end all contact groupings

**Included Contact Type:** 

Round pin single mating end 1st contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.