NSN 5935-00-132-2669

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-132-2669

Body Style:
Straight shape, external coupling
Overall Length:
0.978 inches
Overall Height:
0.938 inches
Overall Width:
0.938 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.719 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.719 inches
Distance From Mounting Shoulder To Front Face:
Between 0.431 inches and 0.441 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Oct-98 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
240.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Rubber single mating end
Torminal Type:

Solder well single mating end single contact grouping

NSN 5935-00-132-2669

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
6 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.030 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0