## NSN 5935-00-132-5662

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-132-5662

**Body Style:** 

Straight shape, flange mount, external coupling

**Overall Length:** 

1.406 inches

**Overall Height:** 

Between 1.115 inches and 1.135 inches

**Overall Width:** 

Between 1.115 inches and 1.135 inches

**Environmental Protection:** 

Moisture proof and salt water resistant and vibration proof

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.906 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.906 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.431 inches and 0.441 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

14-15 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

500.0 single mating end all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:** 

700.0 single mating end all contact groupings

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

**Shell Type:** 

Potting

**Connector Locking Method:** 

Bayonet pin

**Connector Cable Strain Relief Method:** 

Potting type

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

## NSN 5935-00-132-5662

No Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



## **Contact Surface Treatment:** Gold single mating end all contact groupings and silver single mating end all contact groupings **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 14 single mating end 2nd contact grouping **Included Contact Type:** Round socket single mating end all contact groupings **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.015 gold grains, troy and 0.015 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a **Unit Of Measure: Demilitarization:**