NSN 5935-00-132-5737

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-132-5737

Body Style:

Straight shape, flange mount, external coupling

Overall Length:

1.406 inches

Overall Height:

Between 1.302 inches and 1.322 inches

Overall Width:

Between 1.302 inches and 1.322 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.123 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.062 inches

Distance From Mounting Shoulder To Front Face:

Between 0.431 inches and 0.441 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

18-30 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

60.0

Shell Type:

Potting

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Potting type

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

NSN 5935-00-132-5737

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment: Gold single mating end all contact groupings and silver single mating end all contact groupings **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 29 single mating end 2nd contact grouping **Included Contact Type:** Round pin single mating end all contact groupings **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.030 gold grains, troy and 0.030 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A039b0