Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-132-5930

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, thru-hole mount, external coupling
Overall Length:
1.571 inches
Overall Diameter:
Between 1.234 inches and 1.266 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Distance From Mounting Shoulder To Front Face:
0.696 inches
Mounting Facility Thickness:
Between 0.062 inches and 0.125 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
12-10 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Potting
Connector Locking Method:
Bayonet pin
Connector Cable Strain Relief Method:
Potting type
Thready Qty Per Inch (tpi):
20

# NSN 5935-00-132-5930

Electrical Receptacle Connector - Page 2 of 2



# Thread Size:

0.875 inches

#### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

#### Insert Material:

Rubber single mating end

## **Terminal Type:**

Crimp single mating end single contact grouping

#### Shell Material:

Aluminum alloy

#### Shell Surface Treatment:

Cadmium and chromate

#### **Included Contact Quantity:**

10 single mating end single contact grouping

#### **Bushing Accommodation Hole Shape:**

Round

#### Included Contact Type:

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

#### **Precious Material And Weight:**

0.010 gold grains, troy and 0.010 silver grains, troy

#### **Precious Material:**

Gold and silver

#### Thread Series Designator:

Unef

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A039b0