## NSN 5935-00-132-5934

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-132-5934 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, thru-hole mount, external coupling **Overall Length:** 1.853 inches **Overall Diameter:** Between 1.796 inches and 1.828 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Distance From Mounting Shoulder To Front Face:** Between 0.868 inches and 0.900 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.250 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 20-41 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Potting **Connector Locking Method:** Bayonet pin **Connector Cable Strain Relief Method:** Potting type Thready Qty Per Inch (tpi): 18

**Thread Size:** 

1.375 inches

## NSN 5935-00-132-5934

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
41 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.041 gold grains, troy and 0.041 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0