## NSN 5935-00-133-0545

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-133-0545 **Thread Class:** 2a and 2a and 2a **Thread Direction:** Right-hand and right-hand and right-hand **Body Style:** Straight shape, rectangular **Overall Length:** 1.733 inches **Overall Height:** Between 2.865 inches and 2.885 inches **Overall Width:** Between 2.495 inches and 2.505 inches **Environmental Protection:** Humidity resistant and shock resistant and thermal shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.133 inches and 0.165 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.807 inches and 0.817 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.340 inches and 1.360 inches **Threaded Device Type:** Coupling facility and coupling facility and mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 104 single mating end **Polarization Method:** Polarization boss and guide pin/socket Shell Type: Solid **Connector Locking Method:** Thread Length: 0.560 inches **Thread Size:** 0.250 inches **Insert Material:** Plastic diallyl phthalate single mating end or plastic epoxy single mating end **Shell Material:** Aluminum alloy

Shell Surface Treatment: Cadmium and passivate

# NSN 5935-00-133-0545

Electrical Receptacle Connector Body - Page 2 of 2



## **Shell Surface Treatment Specification:**

Qq-p-416, type 2, class 1 federal specification single treatment response

## **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification single material response single response

## **Special Features:**

Polarized at position v

#### **Test Data Document:**

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unf and unef

## **Specification Data:**

96906-ms17779 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

#### Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-m-14 spec.