Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-133-5373

Thread Class:
2a
Za Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
Between 0.630 inches and 0.690 inches
Distance From Mounting Shoulder To Front Face:
Between 0.440 inches and 0.500 inches
Mounting Facility Thickness:
0.093 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thready Qty Per Inch (tpi):
32
Thread Size:
0.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic tetrafluoroethylene single mating end
Terminal Type:
Turret single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Silver
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping

## NSN 5935-00-133-5373

Electrical Receptacle Connector - Page 2 of 2



**Precious Material And Location:** Contact surfaces gold and contact surfaces and shell surfaces silver **Precious Material And Weight:** 0.005 gold grains, troy and 0.105 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0