# NSN 5935-00-133-8607

Electrical Plug Connector - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-00-133-8607 |
|---|
| Body Style:   |
| Straight shape, battery                                       |
| Overall Length:   |
| 4.000 inches  |
| Overall Height:   |
| Between 9.000 inches and 9.500 inches                         |
| Overall Width:  |
| 3.020 inches  |
| Environmental Protection:                                     |
| Shock resistant and moisture resistant                        |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:                           |
| 6 single mating end   |
| Contact Removability:   |
| Removable single mating end all contact groupings             |
| Contact Maximum Current Rating In Amps:                       |
| 200.0 single mating end all contact groupings                 |
| Contact Maximum Ac Voltage Rating In Volts:                   |
| 200.0 single mating end all contact groupings                 |
| Polarization Method:  |
| Contact   |
| Shell Type:   |
| Solid   |
| Connector Cable Strain Relief Method:                         |
| Crimp type  |
| Terminal Location:  |
| Back single mating end all contact groupings                  |
| Contact Material:   |
| Copper alloy single mating end all contact groupings          |
|   |

#### **Contact Surface Treatment:**

Silver single mating end all contact groupings

## Insert Material:

Rubber single mating end

#### **Terminal Type:**

Crimp single mating end all contact groupings

#### **Shell Material:**

Aluminum alloy

### **Shell Surface Treatment:**

Anodize

#### **Insert Material Specification:**

Mil-i-3930 military specification single material response single mating end

# NSN 5935-00-133-8607

A039b0

Mil-i-3930 spec.

Mil-std (military Standard):

Electrical Plug Connector - Page 2 of 2



| Included Contact Quantity:  |  |
|---|--|
| 2 single mating end 1st contact grouping  |  |
| Included Contact Type:  |  |
| Round socket single mating end all contact groupings  |  |
| Special Features:   |  |
| Contact positions e and f shorted together  |  |
| Precious Material And Location:   |  |
| Contact surfaces silver   |  |
| Precious Material And Weight:   |  |
| 0.030 silver grains, troy   |  |
| Precious Material:  |  |
| Silver  |  |
| Test Data Document:   |  |
| 81349-mil-c-7974 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |  |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain         |  |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                           |  |
| Specification Data:   |  |
| 96906-ms25486 government standard   |  |
| Shelf Life:   |  |
| N/a   |  |
| Unit Of Measure:  |  |
| <del></del>   |  |
| Demilitarization:   |  |
| No  |  |
| Fiig:   |  |