# NSN 5935-00-133-8661

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-133-8661 **Body Style:** Straight shape **Overall Length:** 2.088 inches **Overall Height:** 0.802 inches **Overall Width:** 0.494 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** 1.852 inches **Mating End Quantity: Contact Position Arrangement Style:** 13w3 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 5.0 single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 1250.0 single mating end all contact groupings **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings and silver single mating end all contact groupings **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end all contact groupings **Shell Material:** 

Steel

**Shell Surface Treatment:** 

Cadmium and chromate

# NSN 5935-00-133-8661

Electrical Receptacle Connector - Page 2 of 2



#### **Insert Material Specification:**

Mil-m-14, ty sdg military specification single material response single mating end

# **Included Contact Quantity:**

3 single mating end 1st contact grouping

# **Included Contact Type:**

Round socket single mating end 2nd contact grouping

#### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

# **Precious Material And Weight:**

0.013 gold grains, troy and 0.013 silver grains, troy

#### **Precious Material:**

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

**Demilitarization:** 

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-m-14 spec.