NSN 5935-00-134-5304

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-134-5304

Body Style:
T-shape
Overall Length:
0.906 inches
Overall Height:
0.641 inches
Overall Width:
0.250 inches
Environmental Protection:
Corrosion resistant and vibration resistant and shock resistant and moisture resistant
Mating End Quantity:
3
Contact Position Arrangement Style:
Smb all mating ends
Contact Removability:
Nonremovable all mating ends single contact grouping
Contact Maximum Frequency Rating:
10000.0 megahertz all mating ends single contact grouping
Shell Type:
Solid
Connector Locking Method:
Snap ring
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 all mating ends single contact grouping
Contact Material:
Copper alloy all mating ends single contact grouping
Contact Surface Treatment:
Gold and copper all mating ends single contact grouping
Insert Material:
Plastic fluorocarbon all mating ends
Contact Surface Treatment Specification:
Mil-g-45204, type 1 military specification 1st treatment response and mil-c-14550 military specification 2nd treatment response all mating
ends single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response 3rd mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Gold
Shell Surface Treatment Specification:

Shell Material Specification:

Mil-g-45204 military specification single treatment response

Qq-b-626, alloy 360 federal specification single material response

NSN 5935-00-134-5304

Connector Adapter - Page 2 of 2



Insert	Material	Specific	ation:
1113611	water iar	ODECITION	auvii.

L-p-403 federal specification single material response all mating ends

Included Contact Quantity:

1 2nd mating end single contact grouping

Precious Material And Location:

Contact and body surfaces gold

Precious Material And Weight:

0.115 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.