

View Online at <https://aerobasegroup.com/nsn/5935-00-134-5313>

**Body Style:**

Multiple card type

**Overall Length:**

5.405 inches

**Overall Height:**

0.656 inches

**Overall Width:**

0.438 inches

**Environmental Protection:**

Heat resistant and moisture proof and salt water resistant

**Unthreaded Mounting Hole Diameter:**

0.125 inches

**Distance Between Mounting Facility Centers:**

5.093 inches

**Board Accommodated Length:**

2.297 inches all boards

**Board Accommodated Width:**

0.062 inches

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

2 rows of independent contacts inserted board all mating ends

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Contact Maximum Current Rating In Amps:**

5.0 all mating ends all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

1800.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

1500.0 all mating ends all contact groupings

**Polarization Method:**

Fixed inter-contact

**Terminal Location:**

Back all mating ends all contact groupings

**Contact Material:**

Copper alloy all mating ends all contact groupings

**Contact Surface Treatment:**

Gold and nickel all mating ends all contact groupings

**Insert Material:**

Plastic diallyl phthalate all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification 2nd treatment response all mating ends all contact groupings

**Terminal Type:**

Tab, solder lug all mating ends all contact groupings

**Insert Material Specification:**

Mil-m-14 military specification single material response all mating ends

**Included Contact Quantity:**

28 all mating ends all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.056 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.