NSN 5935-00-134-5329

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-134-5329

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Angle, shape, internal coupling
Overall Length:
3.000 inches
Overall Height:
2.060 inches
Overall Diameter:
0.690 inches
Cable Entrance Diameter:
0.250 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
N single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
1100.0 single mating end single contact grouping
Contact Maximum Frequency Rating:
12000.0 megahertz single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Connector Cable Strain Relief Method:
Compression nut
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thread Size:
0.625 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:

Contact Carrace Treatment.

Gold single mating end single contact grouping

NSN 5935-00-134-5329Electrical Plug Connector - Page 2 of 2



Insert Material:
Plastic tetrafluoroethylene single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Shell Surface Treatment Specification:
Qq-n-290, class 1, type 8 federal specification single treatment response
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Special Features:
Accomodates 1/4in. Dia. Semi-rigid coax, army p/n 10185998
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.001 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0