

View Online at <https://aerobasegroup.com/nsn/5935-00-134-5340>

Body Style:

Straight shape, internal coupling

Overall Length:

0.671 inches

Overall Diameter:

0.250 inches

Environmental Protection:

Moisture resistant and vibration resistant

Mating End Quantity:

2

Contact Position Arrangement Style:

C all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

1.5 all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

400.0 all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Snap ring

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic tetrafluoroethylene all mating ends

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold

Included Contact Quantity:

1 2nd mating end all contact groupings

Included Contact Type:

Coaxial pin all mating ends all contact groupings

Precious Material And Location:

Contact surface and shell surface gold

Precious Material And Weight:

0.102 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0