

View Online at <https://aerobasegroup.com/nsn/5935-00-134-5340>

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

0.671 inches

**Overall Diameter:**

0.250 inches

**Environmental Protection:**

Moisture resistant and vibration resistant

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

C all mating ends

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Contact Maximum Current Rating In Amps:**

1.5 all mating ends all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

400.0 all mating ends all contact groupings

**Shell Type:**

Solid

**Connector Locking Method:**

Snap ring

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends all contact groupings

**Contact Material:**

Copper alloy all mating ends all contact groupings

**Contact Surface Treatment:**

Gold all mating ends all contact groupings

**Insert Material:**

Plastic tetrafluoroethylene all mating ends

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Gold

**Included Contact Quantity:**

1 2nd mating end all contact groupings

**Included Contact Type:**

Coaxial pin all mating ends all contact groupings

**Precious Material And Location:**

Contact surface and shell surface gold

**Precious Material And Weight:**

0.102 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0