

View Online at <https://aerobasegroup.com/nsn/5935-00-134-5646>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape

Overall Length:

2.500 inches

Overall Diameter:

1.500 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd 1st mating end

Contact Removability:

Nonremovable all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell and bayonet pin

Thready Qty Per Inch (tpi):

4 and 18

Thread Size:

1.500 inches and 1.125 inches

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Silver all mating ends all contact groupings

Contact Material Specification:

Qq-c-530 or qq-c-533 federal specification single material response all mating ends all contact groupings

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Shell Material Specification:

Qq-b-626, comp 22 federal specification single material response

Included Contact Quantity:

1 2nd mating end all contact groupings

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial socket all mating ends all contact groupings

Precious Material And Location:

Contact surface and shell surface silver

Precious Material And Weight:

0.110 silver grains, troy

Precious Material:

Silver

Test Data Document:

81349-mil-a-27434 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Double stub and unef

Specification Data:

81349-mil-a-27434 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0