Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-134-5743

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
0.974 inches
Overall Height:
1.031 inches
Overall Width:
1.031 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.812 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.812 inches
Distance From Mounting Shoulder To Front Face:
0.380 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
12-8 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
850.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin

NSN 5935-00-134-5743

Electrical Receptacle Connector - Page 2 of 2



Thr	ead Size:
0.68	88 inches
Ter	minal Location:
Bac	ck single mating end single contact grouping
Со	ntact Material:
Cop	oper alloy single mating end single contact grouping
Со	ntact Surface Treatment:
Gol	d single mating end single contact grouping
Ins	ert Material:
Pla	stic diallyl phthalate single mating end
Ter	minal Type:
Crir	np single mating end single contact grouping
She	ell Material:
Alu	minum alloy
Inc	luded Contact Quantity:
8 si	ngle mating end single contact grouping
Inc	luded Contact Type:
Rοι	und socket single mating end single contact grouping
Pre	cious Material And Location:
Cor	ntact surfaces gold
Pre	cious Material And Weight:
0.0	08 gold grains, troy
Pre	cious Material:
Gol	d
Thr	read Series Designator:
Une	əf
She	elf Life:
N/a	
Uni	it Of Measure:
Der	nilitarization:
No	
Fiig	j:
A03	39b0