

View Online at <https://aerobasegroup.com/nsn/5935-00-135-0965>

Thread Class:

2a and 2a and 2b

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

T-shape

Overall Length:

1.125 inches

Overall Height:

0.650 inches

Overall Width:

0.230 inches

Environmental Protection:

Thermal shock resistant and moisture resistant and shock resistant and corrosion resistant and vibration resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

3

Contact Position Arrangement Style:

Bnc all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

1.5 all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

400.0 all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell and externally threaded shell and externally threaded coupling nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

500.0 all mating ends all contact groupings

Thready Qty Per Inch (tpi):

32 and 32 and 32

Thread Size:

0.190 inches and 0.190 inches and 0.190 inches

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Rubber all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 2 military specification single treatment response all mating ends all contact groupings

Contact Material Specification:

Qq-c-530 federal specification single material response all mating ends all contact groupings or qq-c-533 federal specification single material response all mating ends all contact groupings

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold

Shell Surface Treatment Specification:

Mil-g-45204, type 2, cl 2 military specification single treatment response

Shell Material Specification:

Qq-b-613 federal specification single material response or qq-b-626 federal specification single material response

Insert Material Specification:

Mil-r-5847 military specification single material response all mating ends

Included Contact Quantity:

1 2nd mating end single contact grouping

Included Contact Type:

Coaxial socket 3rd mating end single contact grouping

Precious Material And Location:

Contact and body surfaces gold

Precious Material And Weight:

0.103 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf and unf and unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.