

View Online at <https://aerobasegroup.com/nsn/5935-00-135-4180>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling w/strain relief

**Body Length:**

4.880 inches

**Overall Diameter:**

1.968 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and shock resistant and cold resistant and heat resistant and explosion proof

**Cable Entrance Diameter:**

Between 0.611 inches and 0.938 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

28-18 single mating end

**Contact Removability:**

Removable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

22.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

900.0 single mating end 4th contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end 2nd contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling nut

**Connector Cable Strain Relief Method:**

Cable clamp

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.750 inches

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings and nickel single mating end all contact groupings

**Insert Material:**

Rubber single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c, class 1 military specification 1st treatment response single mating end all contact groupings and qq-n-290, class 2 federal specification 2nd treatment response single mating end all contact groupings

**Terminal Type:**

Crimp single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification all treatment responses

**Included Contact Quantity:**

5 single mating end 4th contact grouping

**Included Contact Type:**

Round pin single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.012 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.