

View Online at <https://aerobasegroup.com/nsn/5935-00-135-6908>

**Body Style:**

Angle, shape, internal coupling

**Overall Length:**

0.876 inches

**Overall Height:**

0.782 inches

**Overall Diameter:**

0.375 inches

**Environmental Protection:**

Salt water resistant

**Cable Entrance Diameter:**

0.155 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Sm single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Polarization Method:**

Contact

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Beryllium single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic tetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530, comp a federal specification single material response single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Shell Surface Treatment Specification:**

Qq-s-365, type 2, gr a federal specification single treatment response

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.