NSN 5935-00-136-1919

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-136-1919

Body Style:

Angle, shape, internal coupling

Overall Length:

1.094 inches

Overall Height:

0.750 inches

Environmental Protection:

Salt water resistant

Cable Entrance Diameter:

Between 0.090 inches and 0.115 inches

Mating End Quantity:

4

Contact Position Arrangement Style:

Rf single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1200.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Cable clamp

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-b-626, comp 22 federal specification single material response single mating end single contact grouping

Shell Material:

Copper

NSN 5935-00-136-1919

Mil-g-45204 spec.

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Gold
Shell Surface Treatment Specification:
Mil-g-45204, type 2, cl 2 military specification single treatment response
Shell Material Specification:
Qq-b-626, comp 22, 1/2 h federal specification single material response
Insert Material Specification:
Mil-p-19468 military specification single material response single mating end
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.105 gold grains, troy
Precious Material:
Gold
Test Data Document:
95542-114-104-0004 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):