

View Online at <https://aerobasegroup.com/nsn/5935-00-136-3303>

Body Style:

Straight shape, external coupling

Overall Length:

Between 0.760 inches and 0.800 inches

Overall Height:

1.125 inches

Overall Width:

1.125 inches

Environmental Protection:

Pressure proof and pressure proof and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.116 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.906 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.906 inches

Distance From Mounting Shoulder To Front Face:

Between 0.052 inches and 0.072 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

12-p single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Steel single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Glass single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Shell Material:

Steel

Shell Surface Treatment:

Tin and cadmium

Included Contact Quantity:

15 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Body surfaces gold

Precious Material And Weight:

0.100 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0