Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-136-8342

Thread	Class:
moaa	014001

2a and 2b

**Thread Direction:** 

Right-hand and right-hand

# Body Style:

Straight shape

# **Overall Length:**

0.690 inches

### **Overall Height:**

0.650 inches

**Overall Width:** 

0.190 inches

**Unthreaded Mounting Hole Diameter:** 

0.086 inches

**Distance Between Mounting Facility Centers:** 

0.468 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Removability:

Removable single mating end single contact grouping

# **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Polarization Method:** 

Jackscrew

**Connector Locking Method:** 

Jackscrew-socket

Thready Qty Per Inch (tpi):

56 and 56

Thread Size:

0.086 inches and 0.086 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

### **Insert Material:**

Plastic diallyl phthalate single mating end

# **Terminal Type:**

Crimp single mating end single contact grouping



Included Contact Quantity:

5 single mating end single contact grouping

### Included Contact Type:

Round socket single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.005 gold grains, troy

## **Precious Material:**

Gold

### **Thread Series Designator:**

Unc and unc

Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

## Fiig:

A039b0