Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-137-4256

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
Between 1.318 inches and 1.338 inches
Overall Height:
Between 3.927 inches and 3.947 inches
Overall Width:
Between 3.365 inches and 3.385 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.995 inches and 1.005 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 2.870 inches and 2.880 inches
Distance From Mounting Shoulder To Front Face:
0.750 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
2
Contact Position Arrangement Style:
Lk-20 1st mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
40.0 1st mating end 2nd contact grouping
Shell Type:
Solid
Connector Locking Method:
Screw
Thready Qty Per Inch (tpi):
28
Thread Size:
0.250 inches
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Silver single mating end all contact groupings



Terminal Type: Solder well single mating end all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Included Contact Type:** Round pin single mating end all contact groupings **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.036 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0