NSN 5935-00-137-4524

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-137-4524 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** Between 1.077 inches and 1.117 inches **Overall Diameter:** Between 0.620 inches and 0.630 inches **Distance From Mounting Shoulder To Front Face:** Between 0.515 inches and 0.535 inches **Mounting Facility Thickness:** 0.137 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin Thread Length: 0.318 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Plastic tetrafluoroethylene single mating end

Terminal Type:

Solder well single mating end single contact grouping

NSN 5935-00-137-4524

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Copper alloy
Shell Surface Treatment:
Gold and copper
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Body surface gold and contact surface silver
Precious Material And Weight:
0.100 gold grains, troy and 0.005 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0