## NSN 5935-00-138-3351

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-138-3351

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

Between 0.781 inches and 0.812 inches

**Overall Height:** 

Between 1.173 inches and 1.203 inches

**Overall Width:** 

Between 1.173 inches and 1.203 inches

**Environmental Protection:** 

Moisture resistant and salt water resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.901 inches and 0.911 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.901 inches and 0.911 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.517 inches and 0.547 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

19-33 single mating end

Contact Removability:

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

500.0 single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

Insert Position In Deg:

150.0

Shell Type:

Solid

**Connector Locking Method:** 

Spring friction

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

## NSN 5935-00-138-3351

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
61 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.061 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.