NSN 5935-00-138-5122

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-138-5122 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.719 inches **Overall Diameter:** 0.375 inches **Distance From Mounting Shoulder To Front Face:** 0.578 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping **Thread Size:** 0.190 inches and 0.190 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold and copper single mating end single contact grouping **Insert Material:** Plastic tetrafluoroethylene single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy

Shell Surface Treatment:

Gold and copper

NSN 5935-00-138-5122

Electrical Receptacle Connector - Page 2 of 2



Shell Material Specification: Qq-b-626, comp 22 federal specification single material response **Included Contact Quantity:** 1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact and body surfaces gold

Precious Material And Weight:

0.101 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf and unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0