

View Online at <https://aerobasegroup.com/nsn/5935-00-138-6950>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.532 inches

Overall Height:

Between 2.230 inches and 2.270 inches

Overall Width:

Between 2.230 inches and 2.270 inches

Environmental Protection:

Salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.207 inches and 0.213 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.745 inches and 1.755 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.745 inches and 1.755 inches

Distance From Mounting Shoulder To Front Face:

Between 0.875 inches and 0.891 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

32-17 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

80.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1250.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

315.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.625 inches

Thready Qty Per Inch (tpi):

10

Thread Size:

2.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Rubber single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Double stub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0