Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-139-1639

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Angle shape, external coupling
Overall Length:
0.660 inches
Overall Height: 0.505 inches
Unthreaded Mounting Hole Diameter: 0.102 inches
Cable Entrance Diameter:
0.050 inches
Distance From Mounting Shoulder To Front Face:
0.440 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Sma single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Connector Cable Strain Relief Method:
Crimp type
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
32
Thread Size:
0.216 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping

## NSN 5935-00-139-1639

Electrical Receptacle Connector - Page 2 of 2



Plastic fluoro	carbon single mating end
Contact Surf	face Treatment Specification:
Mil-g-45204,	type 2, class 2 military specification single treatment response single mating end single contact groupin
Terminal Typ	be:
Solder well si	ngle mating end single contact grouping
Contact Mat	erial Specification:
Qq-c-530, co	nd 1/2 hard federal specification single material response single mating end single contact grouping
Shell Materia	al:
Steel comp 3	03
Shell Surface	e Treatment:
Gold	
Shell Surfac	e Treatment Specification:
Mil-g-45204,	type 2, class 1 military specification single treatment response
Shell Materia	al Specification:
Qq-s-763, co	nd a federal specification single material response
Included Co	ntact Quantity:
1 single matir	ng end single contact grouping
Included Co	ntact Type:
Coaxial socke	et single mating end single contact grouping
Special Feat	ures:
2 mtg holes e	equally spaced on a 0.481 in. Mtg flange
Precious Ma	terial And Location:
Contact and s	shell surfaces gold
Precious Ma	terial And Weight:
0.105 gold gr	ains, troy
Precious Ma	terial:
Gold	
Thread Serie	es Designator:
Unef	
Shelf Life:	
N/a	
Unit Of Meas	sure:
Demilitarizat	ion:
No	
Fiig:	
A039b0	
Mil-std (milit	ary Standard):