## NSN 5935-00-139-5733

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-139-5733

**Body Style:** 

Straight edge type w/mounting flange

**Overall Length:** 

4.344 inches

**Overall Height:** 

0.437 inches

**Overall Width:** 

0.328 inches

**Unthreaded Mounting Hole Diameter:** 

0.116 inches

**Distance Between Mounting Facility Centers:** 

4.031 inches

**Board Accommodated Length:** 

3.578 inches single board

**Board Accommodated Width:** 

Between 0.051 inches and 0.071 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of independent contacts inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

10.0 single mating end single contact grouping

**Polarization Method:** 

Contact to contact polarizing keys

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Silver single mating end single contact grouping and gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-19833, type gdi-30 military specification single material response single mating end

**Included Contact Quantity:** 

44 single mating end single contact grouping

**Included Contact Type:** 

Leaf spring single mating end single contact grouping

## NSN 5935-00-139-5733

Electrical Receptacle Connector - Page 2 of 2



Precious	Material	And	Location:
----------	----------	-----	-----------

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.044 gold grains, troy and 0.044 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.