

View Online at <https://aerobasegroup.com/nsn/5935-00-140-0051>

Body Style:

Straight edge type w/mounting flange

Overall Length:

3.250 inches

Overall Height:

0.656 inches

Overall Width:

Between 0.323 inches and 0.333 inches

Unthreaded Mounting Hole Diameter:

Between 0.113 inches and 0.119 inches

Distance Between Mounting Facility Centers:

Between 2.932 inches and 2.942 inches

Board Accommodated Length:

2.479 inches single board and 2.489 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-19833, type gdi-30 military specification single material response single mating end

Included Contact Quantity:

24 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Special Features:

Polarized at contact positions d, e, and p

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.024 gold grains, troy and 0.024 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.