## NSN 5935-00-140-5692

Tip Jack - Page 1 of 2

Plastic insulator **Surface Treatment:** 

Nickel spring



View Online at https://aerobasegroup.com/nsn/5935-00-140-5692 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Natural **Body Style:** Dual threaded bushing mounted **Overall Height:** 0.875 inches **Bushing Accommodation Hole Shape:** Double round plain **Maximum Voltage Rating In Volts:** 2000.0 ac **Accommodated Finger Type:** Banana spring all fingers **Finger Accommodation Diameter:** 0.170 inches and 0.180 inches all fingers **Finger Accommodation Length:** 0.562 inches all fingers **Center To Center Distance Between Finger Accommodations:** 0.750 inches **Bushing Thru-hole Accommodation Diameter:** 0.500 inches Center To Center Distance Between Bushing Thru-hole Accommodations: 0.750 inches **Current Rating In Amps:** 15.0 **Mounting Facility Type And Quantity:** 1 bushing **Thread Size:** 0.250 inches **Terminal Type:** Tab, solder lug Material: Plastic insulator Material:

## NSN 5935-00-140-5692

Tip Jack - Page 2 of 2



	Trea	

Nickel spring

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03400