## NSN 5935-00-140-6280



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-140-6280 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape w/jackscrew **Overall Length:** Between 2.134 inches and 2.174 inches **Overall Height:** 0.835 inches **Overall Width:** Between 0.547 inches and 0.577 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** Between 1.904 inches and 1.924 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 70 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Polarization boss Shell Type:

**Connector Locking Method:** Screw Thready Qty Per Inch (tpi): **Thread Size:** 0.099 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping

## NSN 5935-00-140-6280

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Steel
Included Contact Quantity:
70 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.070 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0