

View Online at <https://aerobasegroup.com/nsn/5935-00-140-8587>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, external/internal coupling

Overall Length:

2.330 inches

Overall Diameter:

1.045 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

N 1st mating end

Contact Removability:

Nonremovable all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded shell and bayonet pin

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Thready Qty Per Inch (tpi):

20

Thread Size:

0.875 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Insert Material:

Plastic polyester glass filled all mating ends or plastic polytetrafluoroethylene all mating ends

Contact Material Specification:

Qq-b-750 federal specification single material response all mating ends single contact grouping or qq-c-530 federal specification single material response all mating ends single contact grouping or qq-c-533 federal specification single material response all mating ends single contact grouping

Shell Material:

Copper alloy

Shell Material Specification:

Qq-b-626 federal specification single material response

Insert Material Specification:

Mil-m-24519 military specification 1st material response all mating ends or l-p-403 federal specification 2nd material response all mating ends

Included Contact Quantity:

1 2nd mating end single contact grouping

Included Contact Type:

Coaxial socket 2nd mating end single contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-24519 spec.