

View Online at <https://aerobasegroup.com/nsn/5935-00-140-8587>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external/internal coupling

**Overall Length:**

2.330 inches

**Overall Diameter:**

1.045 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

N 1st mating end

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded shell and bayonet pin

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends single contact grouping

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.875 inches

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Insert Material:**

Plastic polyester glass filled all mating ends or plastic polytetrafluoroethylene all mating ends

**Contact Material Specification:**

Qq-b-750 federal specification single material response all mating ends single contact grouping or qq-c-530 federal specification single material response all mating ends single contact grouping or qq-c-533 federal specification single material response all mating ends single contact grouping

**Shell Material:**

Copper alloy

**Shell Material Specification:**

Qq-b-626 federal specification single material response

**Insert Material Specification:**

Mil-m-24519 military specification 1st material response all mating ends or I-p-403 federal specification 2nd material response all mating ends

**Included Contact Quantity:**

1 2nd mating end single contact grouping

**Included Contact Type:**

Coaxial socket 2nd mating end single contact grouping

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-24519 spec.