NSN 5935-00-140-8980

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-140-8980 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** Between 2.073 inches and 2.103 inches **Overall Width:** Between 0.479 inches and 0.509 inches **Unthreaded Mounting Hole Diameter:** 0.112 inches **Distance Between Mounting Facility Centers:** Between 1.847 inches and 1.857 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 21 single mating end **Contact Removability:** Removable single mating end 1st contact grouping **Polarization Method:** Mating end Shell Type: Solid **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-g-45204 type 2 class 2 military specification single treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end all contact groupings **Shell Material:**

Steel

NSN 5935-00-140-8980

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 type 2 class 2 federal specification single treatment response
Shell Material Specification:
Qq-s-698 federal specification single material response
Insert Material Specification:
Mil-m-19833 type gdi-30f military specification single material response single mating end
Included Contact Quantity:
20 single mating end 2nd contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.021 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.