Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-140-9048

Thread	Class:
i ili cuu	01400.

2a

**Thread Direction:** 

Right-hand

#### **Body Style:**

Hood, corner opening

#### **Overall Length:**

4.062 inches

#### **Overall Width:**

1.234 inches

**Body Height:** 

2.718 inches

#### **Environmental Protection:**

Fire resistant and vibration resistant

#### **Threaded Device Type:**

## Coupling facility

Mating End Quantity:

1

## Contact Removability:

Removable single mating end single contact grouping

#### **Polarization Method:**

Guide pin/socket

#### **Connector Locking Method:**

Jackscrew

#### Thready Qty Per Inch (tpi):

32

#### Thread Size:

0.138 inches

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

## Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

#### **Terminal Type:**

Crimp and solder single mating end single contact grouping

# Insert Material Specification:

Mil-m-14f, ty sdgf military specification single material response single mating end

# NSN 5935-00-140-9048

Electrical Plug Connector - Page 2 of 2



**Included Contact Quantity:** 90 single mating end single contact grouping Included Contact Type: Hermaphrodite single mating end single contact grouping **Special Features:** No hood on item **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.090 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.