

View Online at <https://aerobasegroup.com/nsn/5935-00-142-0409>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling w/strain relief

Body Length:

2.312 inches

Overall Diameter:

1.484 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and shock resistant and cold resistant and heat resistant and explosion proof

Cable Entrance Diameter:

0.500 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

16s-5 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

215.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Cable clamp

Thread Length:

0.414 inches

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Features Provided:

Pre-tinned terminal

Thready Qty Per Inch (tpi):

20

Thread Size:

1.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping or silver single mating end single contact grouping

Insert Material:

Rubber single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd treatment response single mating end single contact grouping or qq-s-365 federal specification 3rd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.003 gold grains, troy and 0.003 silver grains, troy

Precious Material:

Gold and silver

Test Data Document:

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms3106 government standard

Shelf Life:

N/a

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.