

View Online at <https://aerobasegroup.com/nsn/5935-00-142-0740>

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.457 inches

**Overall Diameter:**

1.156 inches

**Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

14-5 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

20.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

900.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

1250.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Potting

**Connector Locking Method:**

Bayonet latch

**Connector Cable Strain Relief Method:**

Potting type

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Rubber single mating end

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Included Contact Quantity:**

5 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.005 gold grains, troy and 0.005 silver grains, troy

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0