## NSN 5935-00-142-6939

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-142-6939

**Body Style:** 

Straight shape

**Overall Length:** 

Between 2.620 inches and 2.650 inches

**Overall Height:** 

0.660 inches

Overall Width:

Between 0.590 inches and 0.620 inches

**Environmental Protection:** 

Heat resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.125 inches

**Distance Between Mounting Facility Centers:** 

Between 2.401 inches and 2.411 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

50 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Polarization Method:** 

Mating end

Shell Type:

Solid

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, class 4 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Shell Surface Treatment:** 

Cadmium

**Shell Surface Treatment Specification:** 

Qq-p-416, type 2, class 2 federal specification single treatment response

**Insert Material Specification:** 

Mil-m-14, type sdg-f military specification single material response single mating end or mil-m-19833, type gdi-30f military specification single material response single mating end

## NSN 5935-00-142-6939

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
50 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.050 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-24308/8 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.