## NSN 5935-00-145-4746

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-145-4746 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.700 inches **Overall Height:** 0.578 inches **Overall Width:** 0.828 inches **Distance Between Mounting Facility Centers:** 1.400 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 11 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Guide pin/socket Thread Length: 0.250 inches **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** 

\_\_\_\_\_\_\_

Pin single mating end single contact grouping

# NSN 5935-00-145-4746

Electrical Receptacle Connector - Page 2 of 2



### **Insert Material Specification:**

Mil-m-19833, type gdi-30f military specification single material response single mating end

### **Included Contact Quantity:**

11 single mating end single contact grouping

### **Included Contact Type:**

Round pin single mating end single contact grouping

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.