NSN 5935-00-145-9481

Straight shape, internal coupling w/strain relief

Body Style:

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-145-9481

Body Length:
2.753 inches
Overall Diameter:
1.531 inches
Environmental Protection:
Moisture resistant and vibration resistant
Cable Entrance Diameter:
0.625 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
30 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
750.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
Insert Position In Deg: 0.0
0.0
0.0 Shell Type:
0.0 Shell Type: Solid
0.0 Shell Type: Solid Connector Locking Method:
0.0 Shell Type: Solid Connector Locking Method: Bayonet latch
O.0 Shell Type: Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method:
O.0 Shell Type: Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp
O.0 Shell Type: Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Terminal Location:
Shell Type: Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material:
Shell Type: Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Shell Type: Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Shell Type: Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Rubber single mating end
Shell Type: Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Rubber single mating end Terminal Type:

NSN 5935-00-145-9481

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
30 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0