## NSN 5935-00-146-8305

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-146-8305 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 0.917 inches **Overall Diameter:** Between 1.735 inches and 1.765 inches **Environmental Protection:** Moisture resistant and vibration resistant **Distance From Mounting Shoulder To Front Face:** Between 0.691 inches and 0.722 inches **Mounting Facility Thickness:** 0.125 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 18-85 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.250 inches **Terminal Location:** Back single mating end single contact grouping

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

## NSN 5935-00-146-8305

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Silicon single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Included Contact Quantity:
85 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Round pin single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0