## NSN 5935-00-147-0378

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-147-0378 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Thru-hole mount **Overall Length:** 0.532 inches **Bushing Diameter:** 0.500 inches **Overall Diameter:** 0.656 inches **Distance From Mounting Shoulder To Rear Face:** 0.438 inches **Mounting Facility Thickness:** 0.063 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Mh-9 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Contact **Connector Locking Method:** Lever-pivot assembly spring action Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping

**Insert Material:** 

Plastic melamine single mating end

## NSN 5935-00-147-0378

A039b0

Mil-m-14 spec.

Mil-std (military Standard):

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Insert Material Specification:
Mil-m-14, type mme military specification single material response single mating end
Included Contact Quantity:
9 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round keyed
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.009 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: